



# Jinan Yueyu Bearing Import & Export C...



E-TU-TRB-1 5/8 Bearing 2D drawings and 3D CAD models

## TIMKEN E-TU-TRB-1 5/8 Take Up Unit Bearings

Bearing No. E-TU-TRB-1 5/8

Category	Take Up Unit Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	5.484
EAN	0053893532837
Product Group	M06288
Component Description	Take Up Bearing Only
Rolling Element	Tapered Roller Bearing
Housing Style	Unit Only
Mounting Method	Concentric Collar
Compatible Take Up Frame	Not Specified
Adjustment Travel Length	0
Housing Material	Cast Iron
Other Features	Double Row   Double Collar   Wide Slot   Two Lip Seal   Electrodeposition Coating   With Set Screw
Inch - Metric	Inch
Long Description	Take Up Bearing Only; 1-5/8" Bore; 11/16" Slot Width; 4" Slot to Slot Distance; Tapered Roller Bearing; Unit Only; Concentric Collar Mount; Cast Iron Housing Material
Category	Take Up Units
UNSPSC	31171533



## Jinan Yueyu Bearing Import & Export C...

Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Take Up
Manufacturer URL	<a href="http://www.timken.com">http://www.timken.com</a>
Weight / LBS	10
Slot to Slot Distance	4 Inch   101.6 Millimeter
d	1.625 Inch   41.275 Millimeter
Slot Width	0.688 Inch   17.475 Millimeter
Shaft Size	1.625 in
Shaft Size Type	Imperial
Weight	10 lb
UPC Code	053893532837
Dimension B	3-3/8 in
Dimension L	6 in
Dimension A <sub>1</sub>	11/16 in
Dimension L <sub>3</sub>	3-1/4 in
Dimension L <sub>1</sub>	3-13/16 in
Dimension N	1-1/8 in
Dimension L <sub>2</sub>	15/16 in
Dimension N <sub>1</sub>	3/4 in
Dimension H <sub>2</sub>	3-5/16 in
Dimension N <sub>2</sub>	1-15/16 in
Dimension d <sub>1</sub>	3-3/16 in
Dimension H <sub>1</sub>	4 in
Dimension H	4-3/4 in
Dimension A <sub>2</sub>	2-5/16 in
e	0.44
X (if $F_a/F_r \leq e$ )	0.87
Y (if $F_a/F_r \leq e$ )	1.96
X (if $F_a/F_r > e$ )	0.7
Y (if $F_a/F_r > e$ )	2.37



## Jinan Yueyu Bearing Import & Export C...

K Factor	1.36
$C_{90}$ Dynamic Load Rating <sup>1</sup>	7860 lb
$C_0$ Static Load Rating	33000 lb
$F_{a-max}$ Maximum Permissible Thrust Load <sup>2</sup>	2590 lb
$F_{r-max}$ Maximum Allowable Slip Fit Radial Load <sup>3</sup>	6400 lb
Max. Speed <sup>4</sup>	3320 rpm
Note	Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to conditions of slip fit with set screw mounting or in applications where a large moment loading occur